

RENAULT (EU) 15 / 17 R17 TS R1313 (1976-1980)

**ENGINE**

Capacity: 4,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Change every 7500 km/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Classic Multigrade 10W-30	

*Change every 7500 km/ 12 months***TRANSAXLE AUTOMATIC**

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Check every 7500 km, change every 15000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Gearlube RPC 75W-80	SP Gear 5015

*Check every 7500 km, change every 15000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

RENAULT (EU) 15 / 17 R17 TS R1313 (1976-1980)**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.