PRODUCT RECOMMENDATION

ROLLS-ROYCE 20/25/30 HP 20/25 HP <- GKC1-22 (1929-1934)

ENGINE
Capacity: 7,96 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	**Classic Monograde 30**	

Change every 8000 km

AXLE REAR
Capacity: 1,14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Gear ZC 90	**Classic Gear EP 80**	

Change every 16000 km

TRANSMISSION MANUAL 4/1
Capacity: 1,14 liter (Chassis <- GKT 1- 22), Capacity: 2,56 liter (Chassis GKT 1- 22 ->)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	**Classic Monograde 30**	

Change every 16000 km

DISTRIBUTOR LUBRICATOR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Monograde 30		

HAND OILING JOINTS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Monograde 30		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ROLLS-ROYCE 20/25/30 HP 20/25 HP <- GKC1-22 (1929-1934)

PROPELLER SHAFT SLIDING AND JOINTS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Gear ZC 90	**Classic Gear EP 80**	

WHEEL BEARINGS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

WHEEL BEARINGS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

WHEEL HUB SHELL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

COOLING SYSTEM
Capacity: 17,05 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

CHASSIS OIL TANK

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	**Classic Monograde 30**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ROLLS-ROYCE 20/25/30 HP 20/25 HP <- GKC1-22 (1929-1934)

SHOCK DAMPERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		

STEERING BOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

WATER PUMP

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367