ROLLS-ROYCE PHANTOM PHANTOM I

(1925-1931)



ENGINE Capacity: 7,96 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 8000 km

AXLE REAR Capacity: 4,55 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Gear ZC 90	Classic Gear EP 80	
Change every 16000 km		

TRANSMISSION MANUAL 4/1 Capacity: 2,84-3,13 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Gear ZC 90	Classic Gear EP 80		
Change every 16000 km	-		

DISTRIBUTOR LUBRICATOR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

HAND OILING JOINTS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	

ROLLS-ROYCE PHANTOM PHANTOM I

(1925-1931)



PROPELLER SHAFT SLIDING AND JOINTS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Gear ZC 90	Classic Gear EP 80		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
WHEEL BEARINGS FRONT		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
VHEEL BEARINGS REAR		CLIMATE

WHEEL HUB SHELL	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Grease EP 0	

COOLING SYSTEM Capacity: 31,82 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

SHOCK DAMPERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	

ROLLS-ROYCE PHANTOM PHANTOM I

(1925-1931)



STEERING BOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Gear ZC 90	Classic Gear EP 80	

WATER PUMP

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.