

ROLLS-ROYCE PHANTOM PHANTOM V 6.2

(1959-1968)

**ENGINE**

Capacity: 7,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30****PRODUCT RECOMMENDATION 2****Classic Monograde 30***Change every 4000 km***DIFFERENTIAL REAR**

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear MP 90***Check every 8000 km, change every 32000 km***TRANSMISSION AUTOMATIC 4/1**

Capacity: 11,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic ATF A***Check every 4000 km, change every 32000 km***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid DOT 3***Check every 4000 km***POWER STEERING**

Capacity: 1,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic ATF A***Check every 4000 km*

ROLLS-ROYCE PHANTOM PHANTOM V 6.2

(1959-1968)

**COOLING SYSTEM**

Capacity: 13 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.