ROLLS-ROYCE SILVER SHADOW II SILVER SHADOW II (1977-1980)

ENGINE

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		

Change every 10000 km

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Classic Racing Oil 15W-50	**Classic Multigrade 15W-40**	**Classic Multigrade 10W-30**

Change every 10000 km

DIFFERENTIAL REAR
Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 20000 km, change every 40000 km

TRANSMISSION AUTOMATIC
Capacity: 13,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km, change every 20000 km

HYDRAULIC SYSTEM BRAKES/LEVELLING AS OF SERIAL NUMBER 50001

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

ROLLS-ROYCE SILVER SHADOW II SILVER SHADOW II (1977-1980)

HYDRAULIC SYSTEM BRAKES/LEVELLING UP TO SERIAL NUMBER 50000		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING Capacity: 1,7 liter		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM Capacity: 15,9 liter		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant -38 Organic NF	**Coolant -26**	