

ROVER P5 3-LITRE MK II (1962-1965)

**ENGINE**

Capacity: 6,5 liter, Filter capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30****PRODUCT RECOMMENDATION 2****Classic Monograde 30***Check every 1000 km, change every 5000 km***DIFFERENTIAL REAR**

Capacity: 1,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear EP 90***Check every 5000 km, change every 15000 km***OVERDRIVE UNIT**

Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Monograde 30***Check every 5000 km, change every 15000 km***TRANSMISSION AUTOMATIC 3/1**

Capacity: 8,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic ATF A***Check every 5000 km, change every 20000 km***TRANSMISSION MANUAL 4/1**

Capacity: 1,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear EP 90***Check every 5000 km, change every 15000 km*

ROVER P5 3-LITRE MK II (1962-1965)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Check every 5000 km</i>		

POWER STEERING

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		
<i>Check every 1000 km</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Check every 5000 km</i>		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Check every 20000 km, change every 45000 km/ 24 months</i>		

COOLING SYSTEM

Capacity: 13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

ROVER P5 3-LITRE MK II (1962-1965)**CARBURETTOR DAMPER**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Check every 20000 km***FRONT SUSPENSION BALL SWIVEL**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 20000 km***STEERING BOX**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.