SAAB 99 99 TURBO (1978-1980)



ENGINE Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 15W-40	Classic Multigrade 10W-30	

Change every 10000 km/ 6 months

DIFFERENTIAL FROM AUTOMATIC Capacity: 1,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Classic Gear EP 80	Gearlube RPC 75W-80

Check every 10000 km, change every 20000 km

TRANSAXLE AUTOMATIC 3/1 Capacity: 8 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		
Chack avery 10000 km shares avery 200	00 km	

Check every 10000 km, change every 20000 km

TRANSAXLE MANUAL 4/1 Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 15W-40	Classic Multigrade 10W-30	

Check every 10000 km, change every 20000 km

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-S DOT 4	Drauliquid DOT 3	

SAAB 99 99 TURBO (1978-1980)



HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-S DOT 4	Drauliquid DOT 3	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF F	

COOLING SYSTEM Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX WITH POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube RPC 75W-80	SP Gear 5015	

STEERING BOX WITHOUT POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Classic Gear MP 90			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.