SIMCA 1100 1100 5CV (1974-1978)



ENGINE Capacity: 3,3 liter, Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40		

Change every 5000 km

DIFFERENTIAL FRONT Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 5000 km, change every 20000 km		

TRANSMISSION MANUAL 4/1 Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Charle avant 5000 km shanga avant 20000 km	

Check every 5000 km, change every 20000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Object to the COO law also was a constant of the Cooper to the		

Check every 5000 km, change every 20000 km/ 12 months

GREASE POINTS/NIPPLES WHEEL BEARINGS			
Moderate			
RECOMMENDATION 3			
ep Grease EP 2			
:h			

SIMCA 1100 1100 5CV (1974-1978)



COOLING SYSTEM Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 5000 km, change every 50000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.