

SIMCA COUPE 1000/1200 S 1200 S (1967-1971)



ENGINE

Capacity: 4,3 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40*Change every 5000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 5000 km/ 6 months*

TRANSAXLE MANUAL 4/1

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 10000 km*

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 5000 km, change every 20000 km/ 12 months*

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 20000 km*

SIMCA COUPE 1000/1200 S 1200 S (1967-1971)**COOLING SYSTEM**

Capacity: 11 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 5000 km/ 6 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.