

SKODA SERIE 1200 1202 981 (1961-1972)



MOTOR

Kapacitet: 2,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

PRODUKTANBEFALING 2

Classic Monograde 30

Skift alle 2000 km

DIFFERENTIALE BAG

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Classic Gear EP 90

Kontroller alle 2000 km, skift alle 8000 km

GEAR 4/1

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Classic Gear EP 90

Kontroller alle 2000 km, skift alle 8000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

CENTRALT SMØRINGSSYSTEM

Kapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

PRODUKTANBEFALING 2

Classic Monograde 30

Skift alle 100 km

**HJULLEJER BAG**

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 16000 km

HJULLEJER FOR

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 8000 km

SMØREPUNKTER/NIPLER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 2000 km

KØLESYSTEM

Kapacitet: 6 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

STYREHUS

Kapacitet: 0,25 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Classic Gear EP 90		

Kontroller alle 2000 km, skift alle 8000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.