SUNBEAM ALPINE ALPINE SERIES V (1965-1968)



ENGINE Capacity: 4,5 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Classic Monograde 30			
Change every 10000 km			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Multigrade 10W-30		
Character average 10000 km			

Change every 10000 km

DIFFERENTIAL REAR Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear ZC 90	
Change every 10000 km	
USE	CLIMATE

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Change every 10000 km	

USE	LIMATE
Normal Mo	loderate
PRODUCT RECOMMENDATION 1	
Classic Multigrade 15W-40	

Change every 10000 km

SUNBEAM ALPINE ALPINE SERIES V (1965-1968)



TRANSMISSION MANUAL WITH OVERDRIVE 4/1 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		

Change every 10000 km

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 10000 km, change every 60000 km		

 HYDRAULIC CLUTCH SYSTEM

 use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 Image: Climate

 Drauliquid DOT 3
 Image: Climate

Check every 10000 km, change every 60000 km

COOLING SYSTEM Capacity: 7,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 10000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.