

SUZUKI LJ/SJ LJ80 (1977-1983)**ENGINE**

Capacity: 3 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Classic Racing Oil 15W-50****PRODUCT RECOMMENDATION 2****Classic Multigrade 20W-50***Change every 10000 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Multigrade 15W-40****PRODUCT RECOMMENDATION 2****Classic Multigrade 10W-30***Change every 10000 km/ 6 months***DIFFERENTIAL FRONT**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear MP 90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear MP 90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***TRANSFERBOX**

Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear EP 90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

SUZUKI LJ/SJ LJ80 (1977-1983)**TRANSMISSION MANUAL 4/1**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

COOLING SYSTEM

Capacity: 3,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.