PRODUCT RECOMMENDATION SUZUKI LJ/SJ SJ410 (1981-1988)



ENGINE F10A Capacity: 3 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Racing Oil 15W-50	Classic Multigrade 20W-50		
Change every 10000 km/ 6 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Multigrade 10W-30		
	· · ·	· · ·	

Change every 10000 km/ 6 months

DIFFERENTIAL FRONT Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

DIFFERENTIAL REAR Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSFERBOX Capacity: 0,7 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months



TRANSMISSION MANUAL 4/1 Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

COOLING SYSTEM Capacity: 3,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 24 months	•	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.