TOYOTA CROWN S CROWN 2200 DIESEL LS11 (1979-1983)



ENGINE L		
	,8 liter (Service fill), Filter capacity: 1 liter	
JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Bi-Turbo 15W-40		
Change every 5000 km/ 4 months		
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 20W-50
Change every 5000 km/ 4 months		
JSE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Change every 1000 km		
JSE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 20W-50
Change every 1000 km		
DIFFERENTIAL REAR		
Capacity: 1,5 liter		CLIMATE
Capacity: 1,5 liter		climate Moderate
Capacity: 1,5 liter Use Normal PRODUCT RECOMMENDATION 1		
Capacity: 1,5 liter Use Vormal PRODUCT RECOMMENDATION 1		
Capacity: 1,5 liter USE Normal PRODUCT RECOMMENDATION 1 Classic Gear MP 90	nange every 30000 km/ 24 months	
Capacity: 1,5 liter USE Normal PRODUCT RECOMMENDATION 1 Classic Gear MP 90 Check every 15000 km/ 12 months, chapse	nange every 30000 km/24 months	Moderate
Capacity: 1,5 liter USE Normal PRODUCT RECOMMENDATION 1 Classic Gear MP 90 Check every 15000 km/ 12 months, ch	nange every 30000 km/ 24 months	Moderate
Capacity: 1,5 liter USE Normal PRODUCT RECOMMENDATION 1 Classic Gear MP 90 Check every 15000 km/ 12 months, chapse USE Normal PRODUCT RECOMMENDATION 1 Gearlube RPC 75W-80	product recommendation 2 SP Gear 5015	Moderate

TOYOTA CROWN S CROWN 2200 DIESEL LS11 (1979-1983)



TRANSMISSION MANUAL 5/1 Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Check every 15000 km/ 12 months, change e	verv 30000 km/ 24 months

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 7500 km/6 months, change every 30000 k	m/24 months

Check every 7500 km/ 6 months, change every 30000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			

Check every 7500 km/ 6 months, change every 30000 km/ 24 months

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 7500 km/6 months

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 45000 km/ 36 months	·	

TOYOTA CROWN S CROWN 2200 DIESEL LS11 (1979-1983)



WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change eveny 45000 km/ 36 month	1	-

Change every 45000 km/36 months

COOLING SYSTEM Capacity: 9,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 15000 km/ 12 months	;	'

STEERING BOX Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Check every 15000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.