

VAUXHALL CHEVETTE CHEVETTE 1.3 (1975-1984)



ENGINE

Capacity: 2,8 liter, Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50*Change every 10000 km/ 6 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40*Change every 10000 km/ 6 months*

USE

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50*Change every 1000 km*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40*Change every 1000 km*

AXLE REAR

Capacity: 0,65 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 2

SP Gear 5015

VAUXHALL CHEVETTE CHEVETTE 1.3 (1975-1984)



TRANSMISSION AUTOMATIC GM 3-OVH 3/1
Capacity: 6,1 liter (Dry fill), Capacity: 2,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

TRANSMISSION MANUAL 4/1
Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

HYDRAULIC BRAKE SYSTEM
Capacity: 0,54 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM
Capacity: 5,8 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.