

# VAUXHALL CRESTA CRESTA 2.6 PB (1962-1965)



## ENGINE

Capacity: 6,25 liter (Dry fill), Capacity: 5,4 liter (Service fill)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Classic Multigrade 10W-30***Check every 750 km, change every 3000 km*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic Monograde 30***Check every 750 km, change every 3000 km*

## AXLE REAR

Capacity: 2,17 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic Gear EP 90***Check every 3000 km*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 3000 km*

## TRANSMISSION MANUAL 3/1

Capacity: 1,19 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Classic Gear ZC 90***Check every 3000 km*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 3000 km*

# VAUXHALL CRESTA CRESTA 2.6 PB (1962-1965)



## TRANSMISSION MANUAL WITH OVERDRIVE 4/1

Capacity: 2,05 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Classic Gear ZC 90***Check every 3000 km, change every 18000 km*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 3000 km, change every 18000 km*

## HYDRAULIC BRAKE SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 3000 km*

## HYDRAULIC CLUTCH SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Abacot MEP 460***Change every 3000 km*

# VAUXHALL CRESTA CRESTA 2.6 PB (1962-1965)



## WHEEL BEARINGS FRONT

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 18000 km

## COOLING SYSTEM

Capacity: 9,52 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

## STEERING BOX

| USE                       |  | CLIMATE       |
|---------------------------|--|---------------|
| Normal                    |  | Mediterranean |
| PRODUCT RECOMMENDATION 1  |  |               |
| <b>Classic Gear ZC 90</b> |  |               |

Check every 3000 km

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Arctic  |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Classic Gear EP 80</b> |  |         |

Check every 3000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.