

VAUXHALL VICTOR VICTOR 3.3 HC FD

(1967-1972)

**ENGINE**

Capacity: 5,11 liter (Dry fill), Capacity: 4,97 liter (Service fill), Filter capacity: 0,6 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Classic Multigrade 15W-40***Check every 750 km, change every 10000 km/ 3 months***USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30***Check every 750 km, change every 10000 km/ 3 months***AXLE REAR**

Capacity: 2,27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear EP 90***Check every 20000 km/ 6 months***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Classic Gear EP 80***Check every 20000 km/ 6 months***TRANSMISSION AUTOMATIC** GM Powerglide 3 3/1

Capacity: 2,56 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic ATF A***Check every 10000 km/ 3 months, change every 20000 km/ 6 months*

VAUXHALL VICTOR VICTOR 3.3 HC FD

(1967-1972)

**TRANSMISSION MANUAL 3/1**

Capacity: 1,19 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear ZC 90*Check every 20000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 20000 km/ 6 months***TRANSMISSION MANUAL 4/1**

Capacity: 1,36 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear ZC 90*Check every 20000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 20000 km/ 6 months***TRANSMISSION MANUAL WITH OVERDRIVE 4/1**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear ZC 90*Check every 20000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 20000 km/ 6 months*

VAUXHALL VICTOR VICTOR 3.3 HC FD

(1967-1972)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km/ 3 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50000 km/ 15 months*

WHEEL BEARINGS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50000 km/ 15 months*

COOLING SYSTEM

Capacity: 8,35 liter, Capacity: 8,99 liter (+ heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.