

VOLKSWAGEN (VW) (EU) 1500/1600 / TYPE 3 1500S (1963-1965)



MOTOR

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Classic Monograde 30

Skift alle 5000 km/ 6 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

Skift alle 5000 km/ 6 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

HDX 10W

Skift alle 5000 km/ 6 måneder

TRANSAKSEL MANUEL 4/1

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Classic Gear EP 90

Kontroller alle 5000 km, skift alle 25000 km

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Classic Gear EP 80

Kontroller alle 5000 km, skift alle 25000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 250 cm³

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

VOLKSWAGEN (VW) (EU) 1500/1600 / TYPE 3 1500S (1963-1965)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

STYREHUS

Kapacitet: 150 cm3

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.