## **VOLKSWAGEN (VW) (EU) 411/412/ TYPE 4 412** (1972-1974)



Capacity: 3,5 liter (Service fill)		CLIMATE
Normal		Mediterranean
		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 5000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Change every 5000 km/ 6 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 1000 km	<u>'</u>	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Change every 1000 km		
DIFFERENTIAL FROM AUTOMATIC		

Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 10000 km	·

TRANSAXLE MANUAL 4/1 Capacity: 2,5 liter (Dry fill), Capacity: 2 liter (Service fill)				
USE	CLIMATE			
Initial service	Moderate			
PRODUCT RECOMMENDATION 1				
Classic Gear MP 90				
Change every 1000 km				

## VOLKSWAGEN (VW) (EU) 411/412/ TYPE 4 412 (1972-1974)



TRANSMISSION AUTOMATIC 3/1 Capacity: 6 liter (Dry fill), Capacity: 3 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Classic ATF A				
Check every 10000 km, change every 500	00 km			
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
Classic ATF A				
Check every 10000 km, change every 30000 km				

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.