

VOLKSWAGEN (VW) (EU) GOLF I TYPE 17

GOLF 1.5 (51 KW) (1980-1983)



MOTOR JB

Kapacitet: 3,5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Classic Monograde 50

Skift alle 10000 km/ 6 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 20W-50

PRODUKTANBEFALING 3

Classic Multigrade 15W-40

Skift alle 10000 km/ 6 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

HDX 10W

Skift alle 10000 km/ 6 måneder

DIFFERENTIALE FRA EN AUTOMATISK

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

GEAR AUTOMATISK 3/1

Kapacitet: 3 liter (Servicepåfyldning), Kapacitet: 6 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 45000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 30000 km

VOLKSWAGEN (VW) (EU) GOLF I TYPE 17

GOLF 1.5 (51 KW) (1980-1983)



TRANSAKSEL MANUEL 4+E 5/1

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Classic Gear EP 90	Classic Gear EP 80	

TRANSAKSEL MANUEL 4/1

Kapacitet: 1,25 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Classic Gear EP 90	Classic Gear EP 80	

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 24 måneder

KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.