

VOLKSWAGEN (VW) (EU) 1500/1600 / TYPE 3 1500 / 1500N (1961-1965)

**ENGINE**

Capacity: 2,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 5000 km/ 6 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 5000 km/ 6 months*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 5000 km/ 6 months***TRANSAXLE MANUAL 4/1**

Capacity: 2,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km, change every 25000 km*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km, change every 25000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 250 CM3

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

VOLKSWAGEN (VW) (EU) 1500/1600 / TYPE 3 1500 / 1500N (1961-1965)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

STEERING BOX

Capacity: 150 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.