## VOLKSWAGEN (VW) (EU) 1500/1600 / TYPE 3 1600 / 1600L / 1600TL (1965-1973)



ENGINE Capacity: 2,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Change every 5000 km/ 6 months	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 5000 km/ 6 months	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
HDX 10W	
Change every 5000 km/ 6 months	

DIFFERENTIAL FROM AUTOMATIC Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Charle avery 5000 km, change avery 25000 km		

Check every 5000 km, change every 25000 km

_
E
erranean

Check every 5000 km, change every 25000 km

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 5000 km, change every 2500	10 km	·

## VOLKSWAGEN (VW) (EU) 1500/1600 / TYPE 3 1600 / 1600L / 1600TL (1965-1973)



TRANSMISSION AUTOMATIC Capacity: 6 liter (Dry fill), Capacity: 3 liter (\$	Service fill)	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Classic ATF A		
Charle avery E000 km shares avery 2E00	0.4m	

Check every 5000 km, change every 25000 km

HYDRAULIC BRAKE SYSTEM Capacity: 250 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

STEERING BOX Capacity: 150 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.