VOLKSWAGEN (VW) (EU) BEETLE / TYPE 1 BEETLE 11/11A (1946-1953)



ENGINE Capacity: 2,5 liter (Service fill)	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 2500 km	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Change every 2500 km	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
HDX 10W	
Change every 2500 km	
USE	
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 500 km	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Change every 500 km	
USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1 HDX 10W	
Change every 500 km	
USE	 CLIMATE
Second change only	Tropical
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 1500 km	

VOLKSWAGEN (VW) (EU) BEETLE / TYPE 1 BEETLE 11/11A (1946-1953)



USE	CLIMATE
Second change only	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Change every 1500 km	
USE	CLIMATE
Second change only	Arctic
PRODUCT RECOMMENDATION 1	
HDX 10W	
Change every 1500 km	

TRANSAXLE MANUAL 4/1 Capacity: 2-2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 5000 km, change every 2000	0 km	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		

Classic Gear EP 90

Change every 500 km

		1
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

Change every 2500 km

WHEEL BEARINGS FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

Change every 5000 km/ 6 months

VOLKSWAGEN (VW) (EU) BEETLE / TYPE 1 BEETLE 11/11A (1946-1953)



STEERING BOX Capacity: 125 CM3		
USE	CLI	MATE
Normal	Мс	oderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 2500 km		
USE	CLI	MATE
Initial service	Мс	oderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 500 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.