

VOLKSWAGEN (VW) (EU) GOLF I TYPE 17

GOLF 1.5 (51 KW) (1980-1983)

**ENGINE JB**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 20W-50

PRODUCT RECOMMENDATION 3

Classic Multigrade 15W-40*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

HDX 10W*Change every 10000 km/ 6 months***DIFFERENTIAL FROM AUTOMATIC**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90**TRANSAXLE MANUAL 4+E 5/1**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

PRODUCT RECOMMENDATION 2

Classic Gear EP 80**TRANSAXLE MANUAL 4/1**

Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

PRODUCT RECOMMENDATION 2

Classic Gear EP 80

VOLKSWAGEN (VW) (EU) GOLF I TYPE 17

GOLF 1.5 (51 KW) (1980-1983)



TRANSMISSION AUTOMATIC 3/1

Capacity: 6 liter (Dry fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Change every 45000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Change every 30000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Change every 24 months

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.