

# VOLKSWAGEN (VW) (EU) VW-PORSCHE

## 914 914/4 (1969-1973)

**ENGINE**

Capacity: 3,5 liter

## USE

Normal

## CLIMATE

Tropical

## PRODUCT RECOMMENDATION 1

**Classic Multigrade 10W-30***Change every 5000 km/ 6 months*

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Classic Monograde 30***Change every 5000 km/ 6 months***TORQUE CONVERTER**

Capacity: 6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic Monograde 30****TRANSAXLE AUTOMATIC**

Capacity: 2,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic Gear MP 90***Check every 5000 km, change every 20000 km***TRANSAXLE MANUAL 5/1**

Capacity: 2,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic Gear MP 90***Check every 5000 km, change every 20000 km*

# VOLKSWAGEN (VW) (EU) VW-PORSCHE

## 914 914/4 (1969-1973)



### HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*