

VOLVO (EU) 121/122S/220/AMAZON 121 (1956-1958)



MOTOR B16A
Kapacitet: 3,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic Multigrade 10W-30

PRODUKTANBEFALING 2
Classic Monograde 30

Kontroller alle 500 km, skift alle 5000 km

DIFFERENTIALE BAG
Kapacitet: 1,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic Gear MP 90

PRODUKTANBEFALING 2
Gearlube RPC 75W-80

PRODUKTANBEFALING 3
SP Gear 5015

Kontroller alle 5000 km, skift alle 20000 km

GEAR MANUEL H6 3/1
Kapacitet: 0,9 liter

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1
Classic Gear ZC 90

Kontroller alle 5000 km, skift alle 20000 km

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic Gear EP 80

Kontroller alle 5000 km, skift alle 20000 km

HYDRAULISK BREMSESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid DOT 3

VOLVO (EU) 121/122S/220/AMAZON 121 (1956-1958)



SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Kontroller alle 5000 km*

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 40000 km/ 12 måneder*

SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 20000 km*

KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.