

VOLVO (EU) 140 145 S (1968-1968)



MOTOR B18A

Kapacitet: 3,75 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Classic Multigrade 20W-50	Classic Monograde 30	

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Classic Racing Oil 15W-50	Classic Multigrade 15W-40	Classic Multigrade 10W-30

Skift alle 5000 km/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 1,25 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Classic Gear EP 90		

Kontroller alle 5000 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Classic Gear EP 80		

Kontroller alle 5000 km

VOLVO (EU) 140 145 S (1968-1968)



GEAR MANUEL M40 4/1

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Classic Gear ZC 90

Kontroller alle 5000 km, skift alle 40000 km

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear EP 80

Kontroller alle 5000 km, skift alle 40000 km

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 15W-40

PRODUKTANBEFALING 2

Classic Multigrade 10W-30

PRODUKTANBEFALING 3

Classic Monograde 30

Kontroller alle 5000 km, skift alle 40000 km

GEAR MANUEL + OVERGEAR M41 5/1

Kapacitet: 1,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 15W-40

PRODUKTANBEFALING 2

Classic Multigrade 10W-30

PRODUKTANBEFALING 3

Classic Monograde 30

Kontroller alle 5000 km, skift alle 40000 km

SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear LS 90

Kontroller alle 5000 km



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 5000 km

KØLESYSTEM

Kapacitet: 8,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

STYREHUS

Kapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 5015

Kontroller alle 5000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.