

VOLVO (EU) 240 242 DL (1975-1979)



MOTOR B21A

Kapacitet: 3,85 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Classic Multigrade 20W-50

PRODUKTANBEFALING 2

Classic Monograde 30

Skift alle 10000 km/ 6 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 15W-40

PRODUKTANBEFALING 3

Classic Multigrade 10W-30

Skift alle 10000 km/ 6 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

HDX 10W

Skift alle 10000 km/ 6 måneder

ANVEND

Krævende

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Classic Multigrade 20W-50

PRODUKTANBEFALING 2

Classic Monograde 30

Skift alle 5000 km/ 6 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 15W-40

PRODUKTANBEFALING 3

Classic Multigrade 10W-30

Skift alle 5000 km/ 6 måneder

ANVEND

Krævende

KLIMA

Arktisk

PRODUKTANBEFALING 1

HDX 10W

Skift alle 5000 km/ 6 måneder

VOLVO (EU) 240 242 DL (1975-1979)



DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

Kontroller alle 10000 km

GEAR AUTOMATISK BW35 3/1

Kapacitet: 6,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic ATF F

Kontroller alle 10000 km

GEAR MANUEL M45 4/1

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Vintage Gear 90

Kontroller alle 10000 km, skift alle 40000 km

GEAR MANUEL + OVERGEAR M46 5/1

Kapacitet: 2,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Vintage Gear 90

Kontroller alle 10000 km, skift alle 40000 km

SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear LS 90

Kontroller alle 10000 km

**HYDRAULISK BREMSESISTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3*Skift alle 36 måneder***SERVOSTYRING**

Kapacitet: 0,7-1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

PRODUKTANBEFALING 2

Classic ATF A

PRODUKTANBEFALING 3

Classic ATF F*Kontroller alle 10000 km***KØLESYSTEM**

Kapacitet: 9,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 24 måneder***STYREHUS**

Kapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 20W-50

PRODUKTANBEFALING 3

Classic Multigrade 15W-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.