

# VOLVO (EU) 240 245 L (1975-1979)



## MOTOR B19A

Kapacitet: 3,85 liter, Filterkapacitet: 0,5 liter

### ANVEND

Normal

### KLIMA

Middelhavsagtigt

#### PRODUKTANBEFALING 1

**Classic Multigrade 20W-50**

#### PRODUKTANBEFALING 2

**Classic Monograde 30**

*Skift alle 10000 km/ 6 måneder*

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Classic Racing Oil 15W-50**

#### PRODUKTANBEFALING 2

**Classic Multigrade 15W-40**

#### PRODUKTANBEFALING 3

**Classic Multigrade 10W-30**

*Skift alle 10000 km/ 6 måneder*

### ANVEND

Normal

### KLIMA

Arktisk

#### PRODUKTANBEFALING 1

**HDX 10W**

*Skift alle 10000 km/ 6 måneder*

### ANVEND

Krævende

### KLIMA

Middelhavsagtigt

#### PRODUKTANBEFALING 1

**Classic Multigrade 20W-50**

#### PRODUKTANBEFALING 2

**Classic Monograde 30**

*Skift alle 5000 km/ 6 måneder*

### ANVEND

Krævende

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Classic Racing Oil 15W-50**

#### PRODUKTANBEFALING 2

**Classic Multigrade 15W-40**

#### PRODUKTANBEFALING 3

**Classic Multigrade 10W-30**

*Skift alle 5000 km/ 6 måneder*

### ANVEND

Krævende

### KLIMA

Arktisk

#### PRODUKTANBEFALING 1

**HDX 10W**

*Skift alle 5000 km/ 6 måneder*

# VOLVO (EU) 240 245 L (1975-1979)



## DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Classic Gear MP 90**

*Kontroller alle 10000 km*

## GEAR AUTOMATISK BW35 3/1

Kapacitet: 6,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Classic ATF F**

*Kontroller alle 10000 km*

## GEAR MANUEL M45 4/1

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Vintage Gear 90**

*Kontroller alle 10000 km, skift alle 40000 km*

## GEAR MANUEL + OVERGEAR M46 5/1

Kapacitet: 2,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Vintage Gear 90**

*Kontroller alle 10000 km, skift alle 40000 km*

## SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Classic Gear LS 90**

*Kontroller alle 10000 km*



## HYDRAULISK BREMSESISTEM

| ANVEND                       |  | KLIMA   |
|------------------------------|--|---------|
| Normal                       |  | Moderat |
| PRODUKTANBEFALING 1          |  |         |
| <b>Drauliquid DOT 3</b>      |  |         |
| <i>Skift alle 36 måneder</i> |  |         |

## SERVOSTYRING

Kapacitet: 0,7-1,1 liter

| ANVEND                          |                      | KLIMA                |
|---------------------------------|----------------------|----------------------|
| Normal                          |                      | Moderat              |
| PRODUKTANBEFALING 1             | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3  |
| <b>ATF Dexron II-D</b>          | <b>Classic ATF A</b> | <b>Classic ATF F</b> |
| <i>Kontroller alle 10000 km</i> |                      |                      |

## KØLESYSTEM

Kapacitet: 9,5 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |
| <i>Skift alle 24 måneder</i>  |                     |         |

## STYREHUS

Kapacitet: 0,2 liter

| ANVEND                           |                                  | KLIMA                            |
|----------------------------------|----------------------------------|----------------------------------|
| Normal                           |                                  | Moderat                          |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3              |
| <b>Classic Racing Oil 15W-50</b> | <b>Classic Multigrade 20W-50</b> | <b>Classic Multigrade 15W-40</b> |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.