

PRODUCT RECOMMENDATION

VOLVO (EU) 121/122S/220/AMAZON 121 (1961-1967)



ENGINE B18A
Capacity: 3,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|-----------------------------|--|
| Classic Multigrade 10W-30 | Classic Monograde 30 | |

Check every 500 km, change every 5000 km

DIFFERENTIAL REAR
Capacity: 1,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|----------------------------|--------------------------|
| Classic Gear MP 90 | Gearlube RPC 75W-80 | SP Gear 5015 |

Check every 5000 km, change every 20000 km

TRANSMISSION MANUAL M30 4/1
Capacity: 0,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Classic Gear ZC 90 | | |

Check every 5000 km, change every 20000 km

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Classic Gear EP 80 | | |

Check every 5000 km, change every 20000 km

VOLVO (EU) 121/122S/220/AMAZON 121 (1961-1967)


TRANSMISSION MANUAL M40 4/1

Capacity: 0,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Classic Gear ZC 90*Check every 5000 km, change every 20000 km*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km, change every 20000 km*
TRANSMISSION MANUAL + OVERDRIVE M41 5/1

Capacity: 1,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 3

Classic Monograde 30*Check every 5000 km, change every 20000 km*
HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 5000 km*
GREASE POINTS/NIPPLES OTHERS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 5000 km*

VOLVO (EU) 121/122S/220/AMAZON 121 (1961-1967)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 20000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 40000 km/ 12 months

COOLING SYSTEM

Capacity: 8,5 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.