

WOLSELEY 18/85, SIX ADO17 SIX (1972-1975)**ENGINE/TRANSAXLE MANUAL**

Capacity: 10,8 liter, Filter capacity: 0,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 10000 km/ 6 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km/ 6 months, change every 30000 km/ 18 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km/ 6 months, change every 30000 km/ 18 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km/ 6 months*

WOLSELEY 18/85, SIX ADO17 SIX (1972-1975)**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 9,6 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

CARBURETTOR DAMPER

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		

Check every 10000 km/ 6 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 15W-40	Classic Multigrade 10W-30	

*Check every 10000 km/ 6 months***STEERING BOX**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 10000 km/ 6 months

PRODUCT RECOMMENDATION

WOLSELEY 18/85, SIX ADO17 SIX (1972-1975)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.