ANTONIO CARRARO ERGIT SERIES (2090) TF 9400 (2000 AND AFTER)



ENGINE Capacity: 5,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Multifleet SHPD 15W-40	

Check every 8 hours, change every 300 hours

HUB REDUCTIONS FRONT Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 400 hours

HUB REDUCTIONS REAR Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 400 hours

TRANSMISSION FRONT Capacity: 14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Check every 50 hours, change every 400 hours	'

TRANSMISSION REAR Capacity: 17,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Check every 50 hours, change every 4	'

KROON-OIL B.V. Postbus 149 7600 AC Almelo

ANTONIO CARRARO ERGIT SERIES (2090) TF 9400 (2000 AND AFTER)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 50 hours	·	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 50 hours	'	'

COOLING SYSTEM Capacity: 13 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 50 hours, change ever	v 2000 hours/ 24 months	•	

Check every 50 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.