

# ANTONIO CARRARO TIGRETRAC SERIES

## (30) TIGRETRAC TTR 4400 (4WS) (1999 AND AFTER)

**ENGINE**

Capacity: 4,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Check every 8 hours, change every 200 hours***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Change every 50 hours***TRANSMISSION FRONT**

Capacity: 6,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Check every 50 hours, change every 400 hours***TRANSMISSION REAR**

Capacity: 8,5 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Check every 50 hours, change every 400 hours***GREASE POINTS/NIPPLES****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 2****MP Lithep Grease EP 2****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Check every 50 hours*

# ANTONIO CARRARO TIGRETRAC SERIES

## (30) TIGRETRAC TTR 4400 (4WS) (1999 AND AFTER)

**COOLING SYSTEM**

Capacity: 7,6 liter, Capacity: 8,4 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 50 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*