

**BELARUS BX BX 80-2 (1983-1989)****ENGINE MMZ D-50**

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Check every 10 hours, change every 240 hours***TRANSFERBOX**

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 240 hours, change every 960 hours/ 12 months***TRANSMISSION MANUAL 9/2**

Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 240 hours, change every 960 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Check every 10 hours, change every 960 hours/ 12 months***POWER STEERING**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 15***Check every 60 hours, change every 960 hours/ 12 months*

**BELARUS BX BX 80-2 (1983-1989)****GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

**GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

*Change every 960 hours/ 12 months*

**COOLING SYSTEM**

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*