

CASE - IH 94 1294 (1984-1985)**ENGINE**

Capacity: 7,5 liter, Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Multifleet SCD 30****PRODUCT RECOMMENDATION 2****HDX 30***Check every 10 hours, change every 100 hours***USE**

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Multifleet SCD 20W-20****PRODUCT RECOMMENDATION 2****HDX 20W-20***Check every 10 hours, change every 100 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Multifleet SCD 10W****PRODUCT RECOMMENDATION 3****HDX 10W***Check every 10 hours, change every 100 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 800 hours***REDUCTION UNITS FRONT (4x4)**

Capacity: 1,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 800 hours*

CASE - IH 94 1294 (1984-1985)**REDUCTION UNITS REAR (4x2)**

Capacity: 2,3 liter

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gearlube GL-1 80W-90		

*Check every 100 hours, change every 800 hours***TRANSAXLE/HYDRAULIC SYSTEM 12/4**

Capacity: 27,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-1 80W-90		

Check every 50 hours, change every 800 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

*Check every 50 hours, change every 800 hours***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

*Check every 50 hours, change every 800 hours***POWER STEERING**

Capacity: 1,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 50 hours, change every 400 hours

CASE - IH 94 1294 (1984-1985)**GREASE POINTS/NIPPLES OTHERS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 10 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 1000 hours/ 12 months

COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 50 hours, change every 800 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.