

CASE - IH CS CS 120 (1998 AND AFTER)

ENGINE WD 620.84
Capacity: 20 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50	Multifleet SCD 40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Multifleet SHPD 10W-40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 6,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Agrifluid HT	Gearlube GL-5 80W-90

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Agrifluid HT	Gearlube GL-5 80W-90

Check every 500 hours, change every 1000 hours/ 12 months

CASE - IH CS CS 120 (1998 AND AFTER)**HUB REDUCTIONS REAR**

Capacity: 10 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Check every 500 hours, change every 1000 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 40/40**

Capacity: 76 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30***Check every 500 hours, change every 1000 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**LHM +***Check every 50 hours, change every 24 months***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Change every 50 hours***COOLING SYSTEM**

Capacity: 25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2400 hours*

CASE - IH CS CS 120 (1998 AND AFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.