

CASE - IH JXU MAXXIMA JX1100U MAXXIMA (2005 AND AFTER)

**ENGINE**

Capacity: 9,5 liter, Filter capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 10W-40***Check every 10 hours, change every 600 hours***DIFFERENTIAL FRONT**

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 300 hours, change every 1200 hours/ 24 months***HUB REDUCTIONS FRONT**

Capacity: 1,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 300 hours, change every 1200 hours/ 24 months***TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 55 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 300 hours, change every 1200 hours/ 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**LHM +***Check every 10 hours*

CASE - IH JXU MAXXIMA JX1100U MAXXIMA (2005 AND AFTER)



POWER STEERING

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Check every 300 hours, change every 1200 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 14 liter, Capacity: 16 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.