

CASE - IH MAGNUM/MX MAGNUM MX MAGNUM 270 (1999-2002)



MOTOR 6TAA-8304

Kapacitet: 21 liter, Filterkapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 300 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Asyntho 5W-30

PRODUKTANBEFALING 3

Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 300 timer

DIFFERENTIALE FOR

Kapacitet: 15,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 300 timer, skift alle 1200 timer

NAVREDUKTIONER FOR

Kapacitet: 2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 300 timer, skift alle 1200 timer

SELVSPÆRRENDE DIFFERENTIALE FOR

Kapacitet: 15,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 300 timer, skift alle 1200 timer

CASE - IH MAGNUM/MX MAGNUM MX MAGNUM 270 (1999-2002)



TRANSAXSEL/HYDRAULISK SYSTEM

Kapacitet: 172 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 1500 timer

KØLESYSTEM

Kapacitet: 24,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 10 timer, skift alle 2100 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.