

# CASE - IH MAGNUM/MX MAGNUM MAGNUM 310 (2008-2011)

**ENGINE Euro III (CR)**

Capacity: 24,6 liter, Filter capacity: 1,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40***Check every 10 hours, change every 300 hours***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Armado Synth 5W-30****PRODUCT RECOMMENDATION 2****Dieselfleet LSP Ultra 10W-30***Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT**

Capacity: 12,3 liter (with 10 bolts on wheel ends), Capacity: 11,8 liter (with 12 bolts on wheel ends)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Unigear LS GL-3/GL-5 85W-140***Change every 1000 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 1,4 liter (with 10 bolts on wheel ends), Capacity: 3,3 liter (with 12 bolts on wheel ends)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Unigear LS GL-3/GL-5 85W-140***Change every 1000 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 172 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agrifluid HT-Plus***Check every 10 hours, change every 1500 hours*

# CASE - IH MAGNUM/MX MAGNUM MAGNUM 310 (2008-2011)

**COOLING SYSTEM**

Capacity: 26,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12***Check every 10 hours, change every 2100 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*