## CASE - IH PJV, PJN PJV / PJN 55 (2001-2005)



ENGINE Capacity: 6,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 150 hours

DIFFERENTIAL FRONT Capacity: 5 liter (N type), Capacity: 4 liter (V type)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Agrifluid HT-Plus				

Check every 150 hours, change every 1000 hours

HUB REDUCTIONS FRONT Capacity: 0,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 150 hours, change every 1000 hours		

TRANSAXLE/HYDRAULIC SYSTEM (4x2) 16/8 Capacity: 36 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Agrifluid HT-Plus				

Check every 150 hours, change every 1000 hours

TRANSAXLE/HYDRAULIC SYSTEM (4x4) 16/8 Capacity: 38 liter (30 km/h version), Capacity: 43 liter (40 km/h version)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Agrifluid HT-Plus				
Check every 150 hours, change every 1000 hours				

## CASE - IH PJV, PJN PJV / PJN 55 (2001-2005)



## GREASE POINTS/NIPPLES USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Labora Grease Q5 MP Calcep Grease EP 2 MP Lithep Grease EP 2

Check every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.