CASE - IH PJV, PJN PJV / PJN 75 (2001-2005)



ENGINE Capacity: 9,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 5 liter (N type), Capacity: 4 liter (V type)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT		
Check every 150 hours, change every 1000 hours				

HUB REDUCTIONS FRONT
Capacity: 0,5 liter

USE
Normal

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Agrifluid HT-Plus

Agrifluid HT-Plus

Check every 150 hours, change every 1000 hours

TRANSAXLE/HYDRAULIC SYSTEM (4x2) 16/8 Capacity: 36 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT		
Check every 150 hours, change every 1000 hours				

TRANSAXLE/HYDRAULIC SYSTEM (4x4) 16/8 Capacity: 38 liter (30 km/h version), Capacity: 43 liter (40 km/h version)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT		
Check every 150 hours, change every	/ 1000 hours	-		

CASE - IH PJV, PJN PJV / PJN 75 (2001-2005)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Check every 50 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.