

CASE - IH STX STX 275 / STX 275 ACCUSTEER (2000 OG EFTER)



MOTOR CDC 6TAA-8304
Kapacitet: 23,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Asyntho 5W-30

PRODUKTANBEFALING 3
Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE BAG

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

Skift alle 1500 timer/ 12 måneder

DIFFERENTIALE FOR

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

Skift alle 1500 timer/ 12 måneder

GEAR MANUEL/PTO
Kapacitet: 76 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 1500 timer

CASE - IH STX STX 275 / STX 275 ACCUSTEER (2000 OG EFTER)



REDUKTIONSENHEDER BAG

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Skift alle 1500 timer/ 12 måneder

REDUKTIONSENHEDER FOR

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Skift alle 1500 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 178 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 1500 timer

KØLESYSTEM

Kapacitet: 43 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 10 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.