## **CLAAS ARES 600 ARES 656** (2004-2009)



ENGINE DPS Capacity: 14-17 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change even	v 300 hours	

Check every 10 hours, change every 300 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Change every 100 hours

<b>DIFFERENTIAL FRONT</b> A 88-1 Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 300 hours, change every 1200 hours/ 12 months

<b>DIFFERENTIAL FRONT</b> ProActiv 204 Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
01 1 0001	1 / 10 / 1

Check every 300 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 300 hours, change every	S00 hours/ 12 months

## **CLAAS ARES 600 ARES 656** (2004-2009)



POWER TAKE OFF FRONT Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Check every 50 hours, change every 600 hou	rs

TRANSMISSION/HYDRAULIC SYSTEM
Capacity: 65 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Agrifluid HT

CLIMATE

Moderate

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	
	 ·

Check every 10 hours, change every 1200 hours/ 12 months

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
MP Lithep Grease EP 2		
		PRODUCT RECOMMENDATION 2

Check every 50 hours

COOLING SYSTEM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	y 1500 hours/ 24 months	'

## PRODUCT RECOMMENDATION

## **CLAAS ARES 600 ARES 656** (2004-2009)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.