

# CLAAS ARION ARION 650 TIER 4I (2013-2015)



**ENGINE DPS**  
Capacity: 23,5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra 10W-40**

PRODUCT RECOMMENDATION 2

**Agrisynth MSP 10W-40**

PRODUCT RECOMMENDATION 3

**Agridiesel MSP 15W-40**

*Check every 10 hours, change every 500 hours*

## DIFFERENTIAL FRONT

Capacity: 6 liter (20.25 suspension), Capacity: 2,2 liter (20.25SI suspension), Capacity: 6 liter (20.29 suspension), Capacity: 5 liter (20.29SI suspension)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 10 hours, change every 1000 hours*

## HUB REDUCTIONS FRONT

Capacity: 1,5 liter (20.25 suspension), Capacity: 1,5-2 liter (20.25SI suspension), Capacity: 2 liter (20.29 suspension), Capacity: 2 liter (20.29SI suspension)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 10 hours, change every 1000 hours*

## POWER TAKE OFF FRONT

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3

**Agrifluid HT-Plus**

*Check every 50 hours, change every 500 hours*

## TRANSMISSION/HYDRAULIC SYSTEM HEXACTIV

Capacity: 66 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3

**Agrifluid HT-Plus**

*Check every 10 hours, change every 1000 hours*

# CLAAS ARION ARION 650 TIER 4I (2013-2015)



## GREASE POINTS/NIPPLES FRONT AXLE POINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		

## GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.