

**CLAAS AXION AXION 820 (2007-2014)****ENGINE DPS**

Capacity: 22-25 liter

USE		CLIMATE
Normal, fuel sulfur level < 0,2 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Check every 10 hours, change every 500 hours*

USE		CLIMATE
Normal, fuel sulfur level > 0,2 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT**

Capacity: 12 liter (Standard), Capacity: 12 liter (Suspended front axle)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 1 months/ 100 hours, change every 1000 hours***HUB REDUCTIONS FRONT**

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 200 hours, change every 1000 hours***POWER TAKE OFF FRONT**

Capacity: 1,3-1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

*Check every 50 hours, change every 6 months/ 500 hours*

**CLAAS AXION AXION 820 (2007-2014)****TRANSMISSION/HYDRAULIC SYSTEM**

Capacity: 100 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

*Check every 10 hours, change every 1000 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,9 liter (40 km/h version)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>LHM +</b>		

*Check every 10 hours, change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours***COOLING SYSTEM**

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 16</b>		

*Check every 10 hours, change every 1500 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.