

CLAAS AXION AXION 850 HEXASHIFT (2009-2014)

**ENGINE DPS**

Capacity: 22-25 liter

USE

Normal, fuel sulfur level < 0,2 %

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrisynth LSP 10W-40****PRODUCT RECOMMENDATION 2****Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 3****Agridiesel CRD+ 15W-40***Check every 10 hours, change every 500 hours***USE**

Normal, fuel sulfur level > 0,2 %

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrisynth LSP 10W-40****PRODUCT RECOMMENDATION 2****Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 3****Agridiesel CRD+ 15W-40***Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT**

Capacity: 15 liter (Standard), Capacity: 14,5 liter (Suspended front axle)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 1 months/ 100 hours, change every 1000 hours***HUB REDUCTIONS FRONT**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 200 hours, change every 1000 hours***HUB REDUCTIONS REAR**

Capacity: 12,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 500 hours, change every 1000 hours*

CLAAS AXION AXION 850 HEXASHIFT (2009-2014)



POWER TAKE OFF FRONT

Capacity: 1,3-1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 50 hours, change every 6 months/ 500 hours

TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 104 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 10 hours, change every 1000 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter (40 km/h version)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Check every 10 hours, change every 1500 hours/ 24 months

CLAAS AXION AXION 850 HEXASHIFT (2009-2014)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.