

CLAAS AXION AXION 950 STAGE II A23 / B06



MOTOR FPT

Kapacitet: 19,5-27,5 liter

ANVEND

Normalt, svovlniveau i brændstof <0,2 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Armado Synth LSP Ultra 5W-30

PRODUKTANBEFALING 3

Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 600 timer/ 12 måneder

DIFFERENTIALE FOR

Kapacitet: 14 liter (Affjedret foraksel), Kapacitet: 15 liter (Standard)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 1200 timer

GEAR/HYDRAULISK SYSTEM

Kapacitet: 155-165 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 1800 timer

KRAFTOVERFØRING FOR

Kapacitet: 3,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 50 timer, skift alle 600 timer/ 12 måneder

CLAAS AXION AXION 950 STAGE II A23 / B06



NAVREDUKTIONER FOR

Kapacitet: 5 liter (Med bremsen), Kapacitet: 6 liter (Uden bremsen)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 1200 timer

ANVEND

Med bremsen

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 600 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

SMØREPUNKTER/NIPLER FORAKSELPUNKTER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

KØLESYSTEM

Kapacitet: 40 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder/ 1800 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.