

# CLAAS ELIOS ELIOS 210 TIER 3 A 28 (A2800001-) (2010-2014)



## MOTOR FPT

Kapacitet: 9,5 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agridiesel MSP 15W-40**

#### PRODUKTANBEFALING 2

**Agridiesel CRD+ 15W-40**

#### PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

*Skift alle 500 timer*

## DIFFERENTIALE FOR

Kapacitet: 4 liter (30 km/t version), Kapacitet: 5,5 liter (40 km/t version)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

#### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

#### PRODUKTANBEFALING 3

**Gearlube LS 80W-90**

*Skift alle 1000 timer*

## GEAR/HYDRAULISK SYSTEM

Kapacitet: 39-45 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

#### PRODUKTANBEFALING 2

**Agrifluid Synth XHP Ultra**

#### PRODUKTANBEFALING 3

**Agrifluid HT-Plus**

*Skift alle 1000 timer*

## NAVREDUKTIONER FOR

Kapacitet: 0,6 liter (hvert nav)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

#### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

#### PRODUKTANBEFALING 3

**Gearlube LS 80W-90**

*Skift alle 500 timer*

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**SP Matic 2032**

#### PRODUKTANBEFALING 2

**ATF Almirol**

*Skift alle 1000 timer/ 24 måneder*

# CLAAS ELIOS ELIOS 210 TIER 3 A 28 (A2800001-) (2010-2014)



## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

## KØLESYSTEM

Kapacitet: 11 liter (+ kabine), Kapacitet: 10 liter (Uten hytte)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant SP 15+**

PRODUKTANBEFALING 2

**Coolant SP 12**

PRODUKTANBEFALING 3

**Coolant -38 Organic NF***Skift alle 24 måneder/ 1500 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.