

# CLAAS ELIOS ELIOS 220 TIER 3 A 28 (A2800001-)(2010-2014)



## ENGINE FPT

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel MSP 15W-40**

## PRODUCT RECOMMENDATION 2

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40***Change every 500 hours*

## DIFFERENTIAL FRONT

Capacity: 4 liter (30 km/h version), Capacity: 5,5 liter (40 km/h version)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

## PRODUCT RECOMMENDATION 3

**Gearlube LS 80W-90***Change every 1000 hours*

## HUB REDUCTIONS FRONT

Capacity: 0,6 liter (each hub)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

## PRODUCT RECOMMENDATION 3

**Gearlube LS 80W-90***Change every 500 hours*

## TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 39-45 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

## PRODUCT RECOMMENDATION 2

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 3

**Agrifluid HT-Plus***Change every 1000 hours*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol***Change every 1000 hours/ 24 months*

# CLAAS ELIOS ELIOS 220 TIER 3 A 28 (A2800001-)(2010-2014)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 11 liter (+ cabin), Capacity: 10 liter (Without cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Change every 24 months/ 1500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.