CLAAS XERION XERION 3800 SADDLE TRAC (2010 AND AFTER)



ENGINE Caterpillar C9 Capacity: 32 liter		
USE		CLIMATE
Normal, fuel sulfur level 0-1000 ppm		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 400 hours

DIFFERENTIAL Capacity: 18,2 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 400 hours, change every 12 months/ 1600 hours		

PLANETARY GEAR Capacity: 9,5 liter (each)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 400 hours, change every 12 months/ 1600 hours		

POWER TAKE OFF Capacity: 5,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	Agrifluid HT-Plus	
Check every 400 hours, change every 12 months/ 1600 hours		

TRANSMISSION MANUAL GROUN Capacity: 68 liter	ND DRIVE		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Kroontrak CVT 10W-40	Agrifluid HT-Plus		
Check every 10 hours, change ever	v 12 months/ 1600 hours	'	

CLAAS XERION XERION 3800 SADDLE TRAC (2010 AND AFTER)



USE CLIMAT	
	E
Normal Mode	erate
PRODUCT RECOMMENDATION 1	
Perlus HCD 46	

Check every 10 hours, change every 12 months/ 1600 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		

COOLING SYSTEM Capacity: 50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant SP 17
Chook ayany 10 hayra ahanga aya	and 24 months / 2200 hours	

Check every 10 hours, change every 24 months/ 3200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.